




ProSeries™ Plus

SIDE MOUNT SAND FILTER

Powerful Performance. Spherical Design

The pool professional's choice for exceptional filtration in a spherical design. This Pro Series Plus filter incorporates many of the advanced features found in Hayward's Pro Series sidemount filter, delivering high-rate performance for the most demanding installations. Thanks to its spherical design, the Pro Series Plus evenly distributes the high pressure and stress that are common with solar heating systems, spas, fountains and in-floor cleaning systems. Its impressive underdrain assembly uses 3,800 slots on 10 self-cleaning laterals that ensure totally balanced flow and backwashing. The overall result is a minimal-maintenance filter with greater strength and longer life.



Total System: Pumps | **Filters** | Heating | Cleaners | Sanitisation | Automation | Lighting | White Goods



Powerful Performance. Spherical Design.

ProSeries™ Plus Side Mount Sand Filters features and benefits:

- Multilateral Underdrain Assembly– with 360 degree slotted, self-cleaning laterals gives totally balanced flow and backwashing
- Optional Valve and Coupling Selections- for plumbing ease and versatility
- Patented Service-Ease Design- unique folding ball joint design allows lateral assembly to be easily accessed for simple service
- Automatic Air Relief- purges any trapped air during operation of the filtration system
- Integral Sight Glass– To see when the backwash cycle is complete
- Unitised Corrosion- Proof Tank- moulded of tough, durable, colour fast polymeric material for dependable all-weather performance
- Totally Corrosion- Proof Base- is rugged and styled to provide strong, stable support
- Integral Top Diffuser- ensures even distribution of water over the top of the sand media bed
- Integral Moulded Drain Plug- For easy draining of the tank without loss of sand

SPECIFICATIONS- PRO SERIES PLUS SIDE MOUNT SAND FILTERS

FILTER TYPE	High- Rate Sand: No. 1/2 Silica Sand (0.45mm- 0.55mm)
UNDERDRAIN	360 Degree Self-Cleaning Slotted Laterals Precision Installed in Ball-Joint Assembly
CONTROL VALVE	Comes Standard With 2" 7 Position, Vari-Flo Including Unions. Optional: 1 1/2" SKT x 2" SLIP Connectors for Multiple (Tandem) Filter Installations
SUPPORT BASE	Injection-Molded ABS
DIMENSIONS	S311SX: 114cm (W) X 98cm (H) / S360SX: 127cm (W) X 117cm (H) With 2" Multiport Valve Fitted

PERFORMANCE DATA

MODEL NUMBER	FILTRATION AREA	NSF DESIGN FLOW RATE	MAX FLOW RATE	MAXIMUM WORKING PRESSURE	SAND REQUIRED	MAXIMUM TURNOVER (LITRES)	
	m ²	LPM	LPM	KPA	KG	8 HOURS	10 HOURS
S311SX	0.46	375	440	344	159	211,200	264,000
S360SX	0.62	492	530	344	318	254,400	318,000

To take a closer look at Hayward Filters or other Hayward® products, go to www.hayward-pool.com.au or call 1300 POOLS1



P.O. Box 4384 | Dandenong South, VIC, 3164



Hayward and Hayward Energy Solutions are registered trademarks and Easy-Lok and ProSeries are trademarks of Hayward Industries, Inc. © 2016 Hayward Industries, Inc.



30-LTBR-C003